

Coppie di serraggio consigliate

Recommended installation torque

BSPB			
Thread		With O-Ring	Without O-Ring
inch	dash	Nm	Nm
	size	Nominale	Nominale
1/8"	10	15	20
1/4"	13	20	25
3/8"	17	35	35
1/2"	21	50	60
5/8"	23	60	85
3/4"	27	85	115
1"	33	115	140
1.1/4"	42	190	210
1.1/2"	48	240	290
2"	51	300	400

Metrici - Metric			
Thread		Tube	Nm
mm	dash	O.D.	Nm
	size		Nominale
M12x1,5	12	06L	16
M14x1,5	14	08L	16
M16x1,5	16	10L	26
M18x1,5	18	12L	37
M22x1,5	22	15L	47
M26x1,5	26	18L	89
M30x2	30	22L	116
M36x2	36	28L	137
M45x2	45	35L	226
M52x2	52	42L	347
M14x1,5	14	06S	26
M16x1,5	16	08S	42
M18x1,5	18	10S	53
M20x1,5	20	12S	63
M22x1,5	22	14S	79
M24x1,5	24	16S	84
M30x2	30	20S	126
M36x2	36	25S	179
M42x2	42	30S	263
M52x2	52	38S	368

JIC 74°		
Thread	dash	Nm
inch	size	Nominale
	7/16"-20	11
1/2"-20	12	20
9/16"-18	14	30
3/4"-16	19	50
7/8"-14	22	69
1.1/16"-12	27	98
1.3/16"-12	30	118
1.5/16"-12	33	140
1.5/8"-12	41	210
1.7/8"-12	48	290
2.1/2"-12	52	400

ORFS		
Thread	dash	Nm
inch	size	Nominale
	9/16"-18	14
11/16-16	17	24
13/16-16	21	43
1"-14	25	60
1.3/16"-12	30	90
1.7/16"-12	34	125
1.11/16"-12	42	170
2"-12	52	200

FLANGE 61 - 3000		
inch	dash	Nm
inch	size	Nominale
	1/2"	21
3/4"	27	25
1"	33	31
1.1/4"	42	41
1.1/2"	48	52
2"	51	60
2.1/2"	63	85

FLANGE 62 - 6000		
inch	dash	Nm
inch	size	Nominale
	1/2"	21
3/4"	27	29
1"	33	46
1.1/4"	42	69
1.1/2"	48	125
2"	51	208